



SC Type

This is a type that has made the 7 × 7 configuration more flexible. However, assuming that the width is the same, tensile strength is slightly poorer than the 7 × 7 configuration.

Gauge No.	CODE NO.	ROPE	THRED	B S (k g)	B S (N)	B S (l b s)	WEIGHT (g/1000m)	COATED OUT SIDE DIA
#49(7x19)	SC-45	0.45mm	0.03mm	14.9	146.0	35	800	0.60mm
#48(7x19)	SC-60	0.60mm	0.04mm	33.2	325.4	65	1430	0.80mm
#47(7x19)	SC-75	0.75mm	0.05mm	54.0	529.2	100	2170	1.00mm
#46(7x19)	SC-90	0.90mm	0.06mm	73.2	717.4	150	3120	1.20mm
#45(7x19)	SC-105	1.05mm	0.07mm	101.0	989.8	200	4330	1.25mm
#44(7x19)	SC-120	1.20mm	0.08mm	110.0	1078.0	250	5650	1.50mm
#43(7x19)	SC-135	1.35mm	0.09mm	135.0	1323.0	350	7160	1.70mm
#42(1x19)	SC-150	1.50mm	0.10mm	176.6	1730.7	440	9000	1.80mm
#40(7x19)	SC-180	1.80mm	0.12mm	237.1	2323.6	600	13000	